

SAFETY DATA SHEET of: HURACLEAN Acid Super Organic

Revision date: Tuesday, July 7, 2015

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

EXP 71122 - Acid Super Organic

- 1.2 Relevant identified uses of the substance or mixture and uses advised against:
- 1

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

CHRISAL NV

Priester Daensstraat 9 B3920 Lommel Phone: 011548000 — Fax: 011548002 E-mail: info@chrisal.be — Website: http://www.chrisal.be/

1.4 Emergency telephone number:

003270245245

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H302 Acute tox. 4 H314 Skin Corr. 1 H335 STOT SE 3

Classification of the substance or mixture in accordance with regulation 67/548/EC:

R35: Corrosive

2.2 Label elements:

Symbols:



Signal word:

Danger

Hazard statements:

H302 Acute tox. 4:	Harmful if swallowed.
H314 Skin Corr. 1:	Causes severe skin burns and eye damage.
H335 STOT SE 3:	May cause respiratory irritation.

Precautionary statements:

P301+P330+P331:	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312:	Call a POISON CENTER or doctor/physician if you feel unwell.
P403+P233:	Store in a well-ventilated place. Keep container tightly closed.
P405:	Store locked up.
P501:	Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains:

Isotridecanol, ethoxylated Benzotriazol

2.3 Other hazards:

none

3 SECTION 3: Composition/information on ingredients:

Isotridecanol, ethoxylated	5% - 15%	CAS number:	69011-36-5
		EINECS:	
		REACH Registration number:	
		CLP Classification:	H302 Acute tox. 4 H318 Eye Dam. 1
		R-Phrases:	R22 R41
2-(2-butoxyethoxy)ethanol	< 5%	CAS number:	112-34-5
		EINECS:	203-961-6
		REACH Registration number:	01-2119475104-44
		CLP Classification:	H319 Eye Irrit. 2
		R-Phrases:	R36
Benzotriazol	< 5%	CAS number:	95-14-7
		EINECS:	202-394-1
		REACH Registration number:	01-2119979079-20
		CLP Classification:	H302 Acute tox. 4 H318 Eye Dam. 1 H411 Aquatic Chronic 2
		R-Phrases:	R22 R41 R52/53

Urea Hydrochloride	> 30%	CAS number:	506-89-8
		EINECS:	208-059-6
		REACH Registration number:	
		CLP Classification:	H315 Skin Irrit. 2 H319 Eye Irrit. 2 H335 STOT SE 3
		R-Phrases:	R36/37/38

For the full text of the H & R phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact:	remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.
Eye contact:	first prolonged rinsing with water (contact lenses to be removed if this is easily done) then take to physician.
Ingestion: Inhalation:	rinse mouth, do not induce vomiting, take to hospital immediately. let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact:	caustic, redness, pain, serious burns
Eye contact:	caustic, redness, bad looking, pain
Ingestion:	caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach
Inhalation:	headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

none

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

none

5.3 Advice for fire-fighters:

Extinguishing agents to be none avoided:

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up windRemove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

remove by using absorbent material.

6.4 Reference to other sections:

for further information check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

/

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

2-(2-butoxyethoxy)ethanol 67.5 mg/m³

8.2 Exposure controls:

Inhalation protection:	use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	handling with Viton-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:	0 °C
Boiling point/Boiling range:	100 °C — 233 °C
pH:	0.4
pH 1% diluted in water:	1
Vapour pressure/20°C,:	2 332 Pa
Vapour density:	not applicable
Relative density, 20°C:	1.070 kg/l
Appearance/20°C:	liquid
Flash point:	/
Flammability (solid, gas):	not applicable
Auto-ignition temperature:	200 °C
Upper flammability or explosive limit, (Vol %):	24.600 %
Lower flammability or explosive limit, (Vol %):	0.850 %
Explosive properties:	not applicable
Oxidising properties:	not applicable
Decomposition temperature:	1
Solubility in water:	completely soluble
Partition coefficient: n- octanol/water:	not applicable
Odour:	characteristic
Odour threshold:	not applicable
Dynamic viscosity, 20°C:	1 mPa.s
Kinematic viscosity, 20°C:	1 mm²/s
Evaporation rate (n-BuAc = 1):	0.300

9.2 Other information:

Volatile organic component (VOC):	1
Volatile organic component (VOC):	50.397 g/l

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

stable under normal conditions.

10.2 Chemical stability:

extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

none

10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

none

10.6 Hazardous decomposition products:

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

About the preparation itself:	No data available
General information:	See ingredients under section 3
Calculated acute toxicity, LD50 oral rat:	1 900.860 mg/kg
Calculated acute toxicity, LD50 dermal rat:	1

12 SECTION 12: Ecological information:

12.1 Toxicity:

No data available

12.2 Persistence and degradability:

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3 Bioaccumulative potential:

No data available

12.4 Mobility in soil:

Water hazard class, WGK:	2
Solubility in water:	completely soluble

12.5 Results of PBT and vPvB assessment:

No data available

12.6 Other adverse effects:

No data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

The product may be discharged in the indicated percentages of utillization, provided it is neutralised to pH 7. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

not applicable

14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

14.3 Transport hazard class(es):

Class(es):	not applicable
Identification number of the	not applicable
hazard:	

14.4 Packing group:

not applicable

14.5 Environmental hazards:

not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics:	not applicable
Additional guidance:	not applicable

15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK:	2
Volatile organic component (VOC):	1
Volatile organic component (VOC):	50.397 g/l
Composition by regulation (EC) 648/2004:	Nonionic surfactants 5% - 15%

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

Nr.:	number
CAS:	Chemical Abstracts Service
EINECS:	European INventory of Existing Commercial chemical Substances
WGK:	Water hazard class
WGK 1:	slightly hazardous for water
WGK 2:	hazardous for water
WGK3:	extremely hazardous for water
ADR:	Accord européen relatif au transport international des marchandises Dangereuses par Route
TLV:	Threshold Limit Value
PTB:	persistent, toxic, bioaccumulative
vPvB:	very persistent and very bioaccumulative substances
CLP:	Classification, Labelling and Packaging of chemicals
DPD:	Dangerous Preparations Directive

Legend to the R & H Phrases used in the safety data sheet:

 R22: Harmful if swallowed.
 R35: Causes severe burns.
 R36: Irritating to eyes.
 R36/37/38: Irritating to eyes,

 respiratory system and skin.
 R41: Risk of serious damage to eyes.
 R52/53: Harmful to aquatic organisms, may cause

 long-term adverse effects in the aquatic environment.

H302 Acute tox. 4: Harmful if swallowed. H314 Skin Corr. 1: Causes severe skin burns and eye damage.
H315 Skin Irrit. 2: Causes skin irritation. H318 Eye Dam. 1: Causes serious eye damage.
H319 Eye Irrit. 2: Causes serious eye irritation. H335 STOT SE 3: May cause respiratory irritation.
H411 Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Reason of revision, changes of following items:

Sections: 2.1, 2.2

MSDS reference number:

ECM-102496,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 453/2010. Classification has been calculated in accordance with the European directive 67/548/EWG, 1999/45/EC and regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application , the user must carry out a material suitability and safety study himself.